TREND
LIGHT BY SOLID STATE

Miniled XDTL10

10W Recessed Adjustable Downlight

Scan to explore XDTL10 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XDTL10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)	S (Silver)	110V (1-10V)
	4 (4000K)				

Order Code **XDTL104-WB-W-LT**



Product Features

- Recessed adjustable LED downlight with thin trim profile coupled with a low glare conical housing
- Manufactured with an aluminium body and powder coat finish
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with a remote driver

To configure this downlight, please visit
trendlighting.com.au/product/miniled-XDTL10


Product Attributes

LED COB | CRI 90+ | IP20 | CA 90 | L&T DIM

Physical Characteristics

Trim Colour	White | Black | Silver
Tilt Angle	20°
Dimensions	Ø100 x 110 (H) mm
Spring Height	50 mm
Cutout	Circular 92 mm
Weight	255 g

Dimensions (mm)




Cutout Ø92 mm

Technical Characteristics

Based on XDTL104-WB-W-LT

LED Power	10W
LED Type	COB
Lumen Output	1523 lm
Luminous Flux	1067 lm
Efficacy	91.2 lm/W
Colour Temperature	2700K | 3000K | 3500K | 4000K
Colour Technology	CRI 90+ | CRI 93+ VIVID | CRI 97+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours (L80)
Beam Angle	Narrow | Medium | Wide
System Power	11.7W Typical
Driver Model	Trend 150218-300 (L&T)
Input	180-265V AC 50/60 Hz
Output	30-42V DC 300mA
Power Factor	>0.93
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge | DALI | 1-10V

General Characteristics

Category	Downlights
Family	Miniled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	CA90
Ingress Protection	IP20

© Trend Lighting. Specifications are subject to change.

Miniled XDTL10

10W Recessed Adjustable Downlight

Scan to explore XDTL10 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XDTL10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)	S (Silver)	110V (1-10V)
	4 (4000K)				

Order Code **XDTL104-WB-W-LT**

To configure this downlight, please visit
trendlighting.com.au/product/miniled-XDTL10

Trim Colour



W
White Trim



B
Black Trim



S
Silver Trim

© Trend Lighting. Specifications are subject to change.